



part of a day, a week, a month or a whole year, and produce this intern as well as extern. You can prove there is a healthy climate in your production rooms. When the measured values are too high, you can act in time. A little database inside the MACView®-Portable saves the concentrations, temperature, relative humidity, time and date. Up to 630 records could be stored in the memory.

TECHNICAL SPECIFICATIONS

MACView®-Portable

Manufacturer	Environmental Monitoring Systems (EMS) BV (Dutch product)
Material of housing	Plastic ABS
Sensors	Gas- and vapour sensor types available (more the 20 kinds of different sensors available, temperature sensor standard and relative humidity sensor standard available)
Approval	CE
Protection classification	IP55
Dimensions of MACView®-Portable	90 x 48 x 20 mm
Weight	120 gram
Warming-up time	300 seconds
Short-term stability	± 2%
Long-term stability > 1-year	± 5%
Alarms at high measured values	- acoustic: pulsing sound signal - visual: pulsing led
Acceptance of alarm	By accept button
Memory	630 records with build in date- and time 24 hours
Charge time of battery	Maximum of 3 hours with delivered Li-ion charger
Operation time of Li-ion battery	16 hours
Communication with PC	via an RS232-cable
Mounting	The MACView®-Portable can be connected with a clip on a breast pocket or a belt.
Software	MACRegister®-software is standard available for Windows 95, 98, NT, 2000, ME and XP.

Raiffeisenstraat 24
4697 CG Sint-Annaland
The Netherlands

t +31 (0)166 65 72 00
f +31 (0)166 65 72 10

e info@macview.info
i www.macview.info



